

# ***Dynamic 2000***

## **Manual sealless steel strapping tool**

---



### **Characteristics**

---

Strapping qualities:	Regular duty max. 850 N/mm <sup>2</sup> / 123'000 psi
Strapping dimensions:	
widths	12.7 – 20.0 mm / ½ - ¾"
thicknesses	0.38 – 0.58 mm / .015 – .023"
Weight:	3.9 kg / 8.6 lbs
Average seal strength:	approx. 80 %

### **Advantages**

---

- Quality light weight sealless combination tool to strap flat packages (i.e. pallets, bales, crates, cases, various packages)
- Permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals

# Dynamic 2000

## Chart of types Dynamic 2000

---

Item No.	Model	Regular duty steel strapping max. 850 N/mm <sup>2</sup> / 123'000 psi			
		Width		Thicknesses	
		mm	inch	mm	inch
13.2307	Dynamic 2000/12.7/0.38-0.58	12.7	½"	0.38-0.58	.015-.023
13.2308	Dynamic 2000/13/0.38-0.58	13.0		0.38-0.58	.015-.023
13.2309	Dynamic 2000/16/0.38-0.58	16.0	5/8"	0.38-0.58	.015-.023
13.2311	Dynamic 2000/19/0.38-0.58	19.0	¾"	0.38-0.58	.015-.023
13.2312	Dynamic 2000/20/0.38-0.58	20.0		0.38-0.58	.015-.023