

# ***Dynamic 2000***

**Manual sealless steel strapping tool**



**Quality light weight strapping tool for a wide variety of standard, vertical and horizontal applications**

# ***Dynamic 2000***

## Characteristics

## Dynamic 2000

Strapping qualities: Regular duty max. 850 N/mm<sup>2</sup> / 123'000 psi  
 Strapping dimensions: widths 12.7 - 20.0 mm / 1/2 - 3/4"  
 thicknesses 0.38 - 0.58 mm / .015 - .023"  
 Weight: 3.9 kg / 8.6 lbs  
 Average seal strength: approx. 80 %



## Advantages:

- Quality light weight sealless combination tool to strap flat packages (i.e. pallets, bales, crates, cases, various packages)
- Permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals



Item No.	Model	Regular duty max. 850 N/mm <sup>2</sup> / 123'000 psi			
		Width		Thicknesses	
		mm	inch	mm	inch
13.2307	DYNAMIC 2000/12.7/0.38-0.58	12.7	1/2"	0.38-0.58	.015-.023"
13.2308	DYNAMIC 2000/13/0.38-0.58	13.0		0.38-0.58	.015-.023"
13.2309	DYNAMIC 2000/16/0.38-0.58	16.0	5/8"	0.38-0.58	.015-.023"
13.2311	DYNAMIC 2000/19/0.38-0.58	19.0	3/4"	0.38-0.58	.015-.023"
13.2312	DYNAMIC 2000/20/0.38-0.58	20.0		0.38-0.58	.015-.023"