

# P358

## 2-in-1

**Pneumatic, Sealless Strapping Tool  
for HD Applications**



**Developed for PET strap**

with Strap Widths from

16 (5/8") up to 19 (3/4") mm

Max. Tension Force of 2.300 N (517lbs) or 4.000 N (900lbs)

*(tool type dependent)*

## P358

**1-Hand operation. 2-in-1 Pneumatic, Strapping tool for HD PET applications**

**Use it in traditional Manual or Semi-Automatic mode, just by the turn of a knob.**

The P358 of FROMM, is one of the most versatile and reliable industrial Strapping Tools of his kind. Applicable for a wide range of vertical and horizontal transport securing applications with Polyester Strap (PET). It can be operated in either Manual or Semi-Automatic mode. Excellent tool for applications where electrical strapping tools cannot or may not be used. Tension force and welding/cooling time are easy and quick to set and lock by the operator. Resulting in a pleasant to operate and consistent working tool, delivering the same quality of strapping, again and again. Its robust and durable design, with a minimum of moving parts, results in the well known FROMM quality with an unsurpassed long and lean service life.



### Characteristics

Strapping qualities		Polyester (PET) - DIN EN 13394
Strapping dimensions:	<i>widths</i>	16,0 – 19,0 mm / 5/8 – 3/4"
	<i>thicknesses</i>	0,65 – 1,35 mm / .026 – .053"
Weight, <i>without suspension bracket</i>		5,7 kg / 12.6 lbs
Dimensions		L 350 x W 133 x H 135,5 mm/13.8 x 5.2 x 5.3"
Average Seal Strength		Up to 75% (depending of the strap quality)
Strap Tension, <i>See table below</i>		1.000 - 2.300 N / 225-517 lbs
		1.900 - 4.000 N / 427-900 lbs
Tension Speed, <i>See table below</i>		70 or 115 mm/s / 2.7 or 4.5 inch/sec
Power Supply		Compressed air, 5,5 - 6 bar / 80 - 87psi
Air Consumption		4,5 - 9,3NI/s / 0.16 - 0.33 cu.ft/s
Suspension		Suspension Bracket for standard applications, included

### P358 Models

Item No.	Model	Strap width	Strap thickness	Max. Tension	Tension Speed
49.0261	P358/16/0.65-1.05/2.3	16 mm / 5/8"	0.65-1.05 mm / .026 - .041"	2.300N / 517lbs	115 mm/s / 4.5"/s
49.0262	P358/16/0.65-1.05/4.0	16 mm / 5/8"	0.65-1.05 mm / .026 - .041"	4.000N / 900lbs	70 mm/s / 2.7"/s
49.0273	P358/19/0.65-1.35/2.3	19 mm / 3/4"	0.65-1.35 mm / .026 - .053"	2.300N / 517lbs	115 mm/s / 4.5"/s
49.0274	P358/19/0.65-1.35/4.0	19 mm / 3/4"	0.65-1.35 mm / .026 - .053"	4.000N / 900lbs	70 mm/s / 2.7"/s